

Technical data sheet

Product name **ACRILEM 925G**

Short description Waterbased extra-permanent pressure sensitive adhesive

Description Waterbased dispersion of a modified acrylic copolymer.
APEO free.
The product is suitable for:
- paper labels
Adhesive characteristics:
- High adhesion
- High tack
- High cohesion

Typical product properties

<i>Description</i>	<i>Typical Value</i>	<i>Unit of measurement</i>
Appearance	Milky white	
Solids (130°C 1h)	50,0	%
pH	7,0	
Din cup 4 (25°C) viscosity	19,5	s

Typical film properties

<i>Description</i>	<i>Typical Value</i>	<i>Unit of measurement</i>
Peel Adhesion SS 1h coating on polyester	1.200,0	G/25MM
Quick Stick SS coating on polyester	850,0	G/25MM
Shear on SS (25x25 mm) coating on polyester	MIN:30,0	H

Performance and Innovation since 1945

Application

The product is ready to use.

Storage

The product has to be protected from frost and stored at temperatures between +5°C and +35°C. In the correct conditions the product is stable for 6 months from delivery date.

Packing

Bulk
1000 kg container

Notes

These technical data and suggestions are based on information we believe to be reliable and are given in good faith but without any guarantee, as conditions and methods of use of our products are beyond our control. The consumer should apply our products to his own working conditions and determine the suitability of our materials and suggestions before adopting them on a commercial scale. Nevertheless the suggestions concerning the use of our products must not be considered as recommendation for any possible patent violation.