

Technical data sheet

Product name **ACRILEM PS 36-215**

Short description Waterbased permanent pressure sensitive adhesive

Description Aqueous dispersion of an acrylate copolymer.

APEO free.

The product is suitable for:

- medical applications
- synthetic films labels
- textiles-foams

Adhesive characteristics:

- Medium adhesion
- High cohesion
- Medium tack

The product has:

- good water fastness
- very clear film

Typical product properties

<i>Description</i>	<i>Typical Value</i>	<i>Unit of measurement</i>
Appearance	Milky white	
Solids (105°C 1h)	53,0	%
pH	8,5	
Brookfield Viscosity RVT 20°C	500,0	mPa*s

Performance and Innovation since 1945

Typical film properties

<i>Description</i>	<i>Typical Value</i>	<i>Unit of measurement</i>
Peel Adhesion SS 20 min coating on polyester	9,5	N/25MM

Application

The product is ready to use.

Storage

The product has to be protected from frost and stored at temperatures between +5°C and +35°C. In the correct conditions the product is stable for 6 months from delivery date.

Packing

Bulk
1000 kg container

Notes

These technical data and suggestions are based on information we believe to be reliable and are given in good faith but without any guarantee, as conditions and methods of use of our products are beyond our control. The consumer should apply our products to his own working conditions and determine the suitability of our materials and suggestions before adopting them on a commercial scale. Nevertheless the suggestions concerning the use of our products must not be considered as recommendation for any possible patent violation.